

A hard-wax oil finished floor by definition has been saturated throughout with oils that make the floor relatively impermeable to foreign contaminants. Periodic application of DuChâteau® Maintenance Oil Clear rejuvenates the surface coat to prevent desaturation of the hard-wax oils on the wood surface.

# **Drying Time**

Do not touch for the first 12 hours. The optimal hardness is reached after 48 hours. Do not use any water or maintenance products during this period.

## **Working Temperature**

Do not use below 16 degrees Fahrenheit.

#### Coverage

One can (33.8 fl. oz./1L) provides approximately 750 square feet of coverage.

# Storage

Keep container tightly closed and store in a cool, dry place away from direct sunlight. In case of an already opened package, a film could appear on the top layer. The film must be removed before using the product.

#### Frequency of Application

Based on traffic wear patterns, it is recommended to treat the floor at least one to two times a year with Maintenance Oil Clear – more, if necessary.

# **Product Description**

DuChâteau Maintenance Oil Clear is a high-quality floor care product for the regular maintenance of all hard-wax oiled indoor wood surfaces. DuChâteau Maintenance Oil Clear is resistant to wine, beer, cola, coffee, tea, fruit juices, milk and water according to DIN 68861 1 A. This product is also resistant to saliva and sweat according to DIN 53160 and meets all the demands of children's toys according to EN 71.

## **Applications**

Oil finished wood surfaces of any color.

## Instructions for Use

The ground surface must be dry and free of dust, dirt and grease. Clean the wood surface with DuChâteau Premium Floor Cleaner & Protectant. Let dry properly. DuChâteau Maintenance Oil Clear is now ready to use. Stir well. As with all wood finishing floor care products, always test the oil in an inconspicuous area first to safeguard against an undesirable outcome. Once confirmed satisfactory, apply a thin layer of DuChâteau Maintenance Oil Clear evenly along the grain; if excessive Maintenance Oil Clear is applied, it will not cure. Allow oil to impregnate for a few minutes. Afterwards, wipe the surface with a white clean cloth to remove excess oil.

For more detailed instructions and videos, visit duchateau.com.

1888 DUCHATEAU · DUCHATEAU.COM

Please note this current Maintenance Oil Clear replaces the previous maintenance oil, which is no longer available for purchase. This technical data sheet is merely a guide and not a guarantee.